

# B

## NumPy Visual Guide

**Lab Objective:** *NumPy operations can be difficult to visualize, but the concepts are straightforward. This appendix provides visual demonstrations of how NumPy arrays are used with slicing syntax, stacking, broadcasting, and axis-specific operations. Though these visualizations are for 1- or 2-dimensional arrays, the concepts can be extended to n-dimensional arrays.*

### Data Access

The entries of a 2-D array are the rows of the matrix (as 1-D arrays). To access a single entry, enter the row index, a comma, and the column index. Remember that indexing begins with 0.

$$A[0] = \begin{bmatrix} \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \end{bmatrix} \quad A[2,1] = \begin{bmatrix} \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \end{bmatrix}$$

### Slicing

A lone colon extracts an entire row or column from a 2-D array. The syntax `[a:b]` can be read as “the *a*th entry up to (but not including) the *b*th entry.” Similarly, `[a:]` means “the *a*th entry to the end” and `[:b]` means “everything up to (but not including) the *b*th entry.”

$$A[1] = A[1,:] = \begin{bmatrix} \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \end{bmatrix} \quad A[:,2] = \begin{bmatrix} \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \end{bmatrix}$$
$$A[1:,:2] = \begin{bmatrix} \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \end{bmatrix} \quad A[1:-1,1:-1] = \begin{bmatrix} \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \\ \times & \times & \times & \times & \times \end{bmatrix}$$

## Stacking

`np.hstack()` stacks sequence of arrays horizontally and `np.vstack()` stacks a sequence of arrays vertically.

$$A = \begin{bmatrix} \times & \times & \times \\ \times & \times & \times \\ \times & \times & \times \end{bmatrix} \quad B = \begin{bmatrix} * & * & * \\ * & * & * \\ * & * & * \end{bmatrix}$$

$$\text{np.hstack}((A,B,A)) = \begin{bmatrix} \times & \times & \times & * & * & * & \times & \times & \times \\ \times & \times & \times & * & * & * & \times & \times & \times \\ \times & \times & \times & * & * & * & \times & \times & \times \end{bmatrix}$$

$$\text{np.vstack}((A,B,A)) = \begin{bmatrix} \times & \times & \times \\ \times & \times & \times \\ \times & \times & \times \\ * & * & * \\ * & * & * \\ * & * & * \\ \times & \times & \times \\ \times & \times & \times \\ \times & \times & \times \end{bmatrix}$$

Because 1-D arrays are flat, `np.hstack()` concatenates 1-D arrays and `np.vstack()` stacks them vertically. To make several 1-D arrays into the columns of a 2-D array, use `np.column_stack()`.

$$x = [\times \quad \times \quad \times \quad \times] \quad y = [* \quad * \quad * \quad *]$$

$$\text{np.hstack}((x,y,x)) = [\times \quad \times \quad \times \quad \times \quad * \quad * \quad * \quad * \quad \times \quad \times \quad \times \quad \times]$$

$$\text{np.vstack}((x,y,x)) = \begin{bmatrix} \times & \times & \times & \times \\ * & * & * & * \\ \times & \times & \times & \times \end{bmatrix} \quad \text{np.column_stack}((x,y,x)) = \begin{bmatrix} \times & * & \times \\ \times & * & \times \\ \times & * & \times \\ \times & * & \times \end{bmatrix}$$

## Broadcasting

NumPy automatically aligns arrays for component-wise operations whenever possible. See <http://docs.scipy.org/doc/numpy/user/basics.broadcasting.html> for more in-depth examples and broadcasting rules.

$$A = \begin{bmatrix} 1 & 2 & 3 \\ 1 & 2 & 3 \\ 1 & 2 & 3 \end{bmatrix} \quad x = [10 \quad 20 \quad 30]$$

$$A + x = \begin{bmatrix} 1 & 2 & 3 \\ 1 & 2 & 3 \\ 1 & 2 & 3 \\ + \\ 10 & 20 & 30 \end{bmatrix} = \begin{bmatrix} 11 & 22 & 33 \\ 11 & 22 & 33 \\ 11 & 22 & 33 \end{bmatrix}$$

$$A + x.\text{reshape}((1,-1)) = \begin{bmatrix} 1 & 2 & 3 \\ 1 & 2 & 3 \\ 1 & 2 & 3 \end{bmatrix} + \begin{bmatrix} 10 \\ 20 \\ 30 \end{bmatrix} = \begin{bmatrix} 11 & 12 & 13 \\ 21 & 22 & 23 \\ 31 & 32 & 33 \end{bmatrix}$$

## Operations along an Axis

Most array methods have an `axis` argument that allows an operation to be done along a given axis. To compute the sum of each column, use `axis=0`; to compute the sum of each row, use `axis=1`.

$$A = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \end{bmatrix}$$

$$A.\text{sum}(\text{axis}=0) = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \end{bmatrix} = [4 \quad 8 \quad 12 \quad 16]$$

$$A.\text{sum}(\text{axis}=1) = \begin{bmatrix} 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \\ 1 & 2 & 3 & 4 \end{bmatrix} = [10 \quad 10 \quad 10 \quad 10]$$